



Features/Advantages	Description	Applications
<ul style="list-style-type: none"> PVC jacket, CM rated Four individually bonded pairs Termination per IEEE specification T568B wiring Assembled in USA using US-made cable stock 100% tested and individually certified performance 	<p>These Cat 5e and Cat5e + cables are fitted with etherCon carriers to fit ETS InstaSnake audio adapters. Each assembly is made with US-made Belden cable, and is fully certification-tested to ensure specification compliant performance for return loss and crosstalk.</p> <p>The etherCon cable carriers provide excellent strain relief to ensure that flexion or pulling on the cable will not compromise connection integrity -- resulting in consistent, reliable performance in the field in any application from audio to data.</p> <p>Belden Cable: The 1305A and 1700A are unshielded cable. The 1533R is shielded cable.</p> <p>Blue Jeans Cable: BJC unshielded Cat6 is also available.</p> <p>All cables come in black and grey colors.</p>	<ul style="list-style-type: none"> Patch cables Analog and Digital Audio NTSC/PAL component or composite video Digital Video Premise Horizontal cable Gigabit Ethernet and 100BaseTx

Specifications		Product Ordering Information	
Bandwidth	Audio to 250 MHz	1305A-025-XX	25 ft 1305A cable with etherCon cable carriers
Connectors	RJ45 plug to RJ45 plug with etherCon cable Carrier on both ends	1305A-050-XX	50 ft 1305A cable with etherCon cable carriers
		1305A-100-XX	100 ft 1305A cable with etherCon cable carriers
Impedance	100 ohms +/- 10	1305A-200-XX	200 ft 1305A cable with etherCon cable carriers
Outer Shield	Aluminum foil-polyester tape and 24AWG Drain wire (for 1533R)	1533R-025-XX	25 ft 1533R cable with etherCon cable carriers
		1533R-050-XX	50 ft 1533R cable with etherCon cable carriers
		1533R-100-XX	100 ft 1533R cable with etherCon cable carriers
		1533R-200-XX	200 ft 1533R cable with etherCon cable carriers
Conductors	24 AWG solid (for 1533R and 1700A) 24 AWG 7x32 stranded (for 1305A) flexible, tactical (rugged) for field & stage applications	1700A-025-XX	25 ft 1700A cable with etherCon cable carriers
		1700A-050-XX	50 ft 1700A cable with etherCon cable carriers
		1700A-100-XX	100 ft 1700A cable with etherCon cable carriers
Operating Temp	-20 degrees C to +75 degrees C	1700A-200-XX	200 ft 1700A cable with etherCon cable carriers
Cable Diameter	0.20 in (1700A), 0.26in (1533R) & BJ Cat6, 0.30in (1305A)		
Pulling Tension	25 lbs recommended	BJCCat6-025-XX	25 ft BJCCat6 cable with etherCon cable carrier
Testing	TIA/ISO Cat5e certified	BJCCat6-050-XX	50 ft BJCCat6 cable with etherCon cable carriers
		BJCCat6-100-XX	100 ft BJCCat6 cable with etherCon cable carriers
		BJCCat6-200-XX	200 ft BJCCat6 cable with etherCon cable carriers
		<u>Notes:</u>	1. XX is for cable color; -BK for Black - GR for Gray
			2. Other lengths are available upon request.

September 2015



Energy Transformation Systems, Inc.
 43353 B Osgood Road, Fremont, CA 94539
 www.etslan.com
 800-752-8208 510-656-2012 Fax 510-656-2026

