


InstaSnake PA200™ Series

Audio Products - Adapters



Features/Advantages	Description	Applications
<ul style="list-style-type: none"> Easily transported Low cost Add second unit to increase the number of channels May be used for analog or digital audio – mic or line level Supports 48V phantom power Rugged, 'road-ready' construction RoHS compliant USA Made - 100% tested 	<p>The ETS InstaSnake™ Series (PA205F or M) is a compact, lightweight, versatile passive component allowing you to run audio signals over a single run of Cat 5, 5e, 6 or 6a UTP cables. With a roll of cable, these compact units are easily transported and/or stored solving dozens of live and/or recording sound problems.</p> <p>The InstaSnake is a passive unit, so you do not need power. The InstaSnake accepts “mic” level or line level analog or digital audio. The basic units are a pair of passive units with bi-directional capability which can be input directly into analog or digital consoles.</p> <p>Designed to the highest professional standards the InstaSnake has a wide, flat frequency response, low THD and residual noise. The InstaSnake has been factory tested to 1900 feet using balanced line low impedance dynamic microphones and up to 850 ft. with phantom power over Cat5. Both send and receive units can be mounted on the wall or on the floor.</p> <p>The PA205F or PA205M model sacrifices one pair for a ground to support phantom power on UTP (unshielded twisted pair) data cable and has three connectors and an Ethercon RJ45 jack.</p> <p>Note: When using with the Cat5 or better UTP (T568B wiring) the PA205 is Clear-Com products compatible.</p>	<ul style="list-style-type: none"> Live Sound Recording Studios TV & Radio Broadcasts Production/Post Production Houses Foley/ADR Studios Hotels Convention Centers Churches Cruise Ships Auditoriums/Stadiums Home Studios Remote & News Trucks Field Recording

Specifications		Product Ordering Information	
Crosstalk @ 20KHz	-109dB between Ch1 and Ch2 -102dB between Ch1 and Ch3 -106dB between Ch2 and Ch3	PA205F PA205M	(3) FXLR to Ethercon RJ45 jack (3) MXLR to Ethercon RJ45 jack
Distance	UTP – 1900 ft 850 ft – Phantom Power		
Connectors	Female or Male XLR to Ethercon RJ45		
Dimensions L x W x H	72 x 110mm x 42mm		
Weight	0.32 Kg		

© Copyright 2005-2014 Energy Transformation Systems, Inc.
 FatCat5 System panels and information outlets protected under US Patent Number 6,123,577. FatCat5™, FatCat5 System™, Chameleon Color Coding System™, Balanced Star™, Balanced Line™, Monoline™ and Precision Wave™, InstaSnake™, CineSnake™ are trademarks of Energy Transformation Systems. All other brand or product names are or may be trademarks of, and are used to identify the products or services of their respective owners.

Revised 4/24/18



Energy Transformation Systems, Inc.

43353 B Osgood Rd. Fremont, CA 94539
 800-752-8208 510-656-2012 Fax 510-656-2026